


GPW115-AU

Outward Opening Window



Opening Types



Flat-panel Design

Flush frame and sash, no level difference, cleaner lines.



Seamless Welding

Seamless Welding technology, providing greater strength and more beautiful appearance.



Mosquito Screen

48 Mesh High Transmittance Screen



Concealed Handle

LEAWOD customized folding handle make concise appearance.



Non-return Drainage System

Non-return drainage system prevent water and pests from entering.



Ultra-narrow Screen Design

The inward-opening screen that can be equipped with either 48 Mesh High Transmittance Screen or Stainless Steel Screen to meet insect prevention needs.



Section	Item	Standard Configuration	
① Depth of Profile: 115mm ② Visible Width: 79mm ③ Frame Width: 23mm ④ Sash Width: 50mm ⑤ Frame Width: 51mm ⑥ Sash Width: 49mm	Profile	Profile Thickness:115mm Thickness: ≥1.80mm	
	Screen	48 Mesh High Transmittance Screen/304 /316Stainless Steel Screen(Inward-opening)	
	Surface Treatment	Standard Powder: Autria Tiger Powder Spraying	
		Optional Powder: 10/15-Year Weathering-Resistant Fluorocarbon Powder or 20-Year Weathering-Resistant Fluorocarbon Powder	
		Powder Recommendation: Optional Configurations for Coastal Areas/High UV-exposure Regions	
	Glass	Fixed: 5mm+20Ar+5mm Glass Rabbet:35mm Sash: 5mm+20Ar+5mm Glass Rabbet:40mm	
Hardware	Mosquito Net	Handle: Germany HOPPE Transmission: Germany G-U	
	Glass Sash	Handle: LEAWOD Transmission: Germany G-U	
Technologies	Aluminum	Seamless Welding of Sash and Frame/Cavity Foam Filling of Frame/Non-return Drainage System	