
GXN120-P3

Inward-opening Window with Integrated Screen



Opening Types





Profile Ultra-narrow Design

Ultra-narrow profile design, with multiple options available for the fixed-glass glazing bead.



Flush Frame and Sash

The flush design of the interior frame and sash gives the window a smoother and more aesthetically pleasing appearance.



35.3mm Ultra-wide Thermal Break Strip

The extrawide thermal break helps save energy more easily, and the isothermal design creates a solid structural basis for high efficiency.



Screen Sashes Open Inward

The screen sash is easy to clean, and the concealed button adds to its sleek, refined look.



Fully Welded Glazing bead


Strengthens corner structure and prevents warping over time, boosts sealing and installation stability,



Triple Glazing with Two Insulating Air Spaces

Standard configuration includes triple glazing with two air cavities for enhanced energy efficiency, and glass upgrades are also available to meet specific requirements.



Section	Item	Standard Configuration	
In  Out ① Depth of Profile: 120mm ② Visible Width: 74mm ③ Frame Width: 15mm ④ Sash Width: 53mm ⑤ Frame Width: 54mm ⑥ Screen Width: 18mm ⑦ Visible Width: 75mm	**Profile**	Profile Thickness: 120mm Thickness: ⩾1.8mm	
	Screen	48 Mesh High Transmittance Screen	
	Surface Treatment	Standard Powder: Autria Tiger Powder Spraying	
		Optional Powder: 10/15-Year Weathering-Resistant Fluorocarbon Powder or 20-Year Weathering-Resistant Fluorocarbon Powder	
		Powder Recommendation: Optional Configurations for Coastal Areas/High UV-exposure Regions	
	Glass	Fixed: 5mm+12Ar+5mm12Ar+5mm Glass Rabbet:50mm	
		Sash: 5mm+12Ar+5mm12Ar+5mm Glass Rabbet:48mm	
	Hardware	Sash Handle: HOPPE	
		Screen HandleLEAWOD	
		Transmission: SIEGENIA	
	Technologies	Aluminum	Frame & sash: Seamless Weld Frame:Foam Filling Sash:Non-foam Filling Fully Welded Glazing Bead