
GXW105

Outward-opening Window with Integrated Screen



Opening Types





Ultr-anarrow Sightline

The ultr-anarrow design maximizes natural light intake while delivering a simple yet refined visual appearance.



Integrated Screen and Sash

Space-saving, seamless, easy-clean, bug-proof, and drop-safe.



R3 Corner Design

No sharp edges or corners, ensuring user safety during operation.



LEAWOD Custom Handle

German-imported Hoppe handles are optionally available, catering to personalized demands for handle feel and appearance.



Non-return Drainage System


Hidden drainage channels and a unique cavity design use inside-outside pressure differences to let rainwater drain away freely without blockage.



Multi-color Configuration

We can customize colors according to customer requirements, with more than 100 colors currently available.



Section	Item	Standard Configuration
In  Out ① Depth of Profile: 105mm ② Visible Width: 86mm ③ Frame Width: 15mm ④ Screen Width: 65mm ⑤ Frame Width: 54mm ⑥ Sash Width: 80mm ⑦ Visible Width: 140mm	Profile	Profile Thickness: 105mm Thickness: ⩾1.8mm
	Screen	48 Mesh High Transmittance Screen
	Surface Treatment	Standard Powder: Autria Tiger Powder Spraying
		Optional Powder: 10/15-Year Weathering-Resistant Fluorocarbon Powder or 20-Year Weathering-Resistant Fluorocarbon Powder
		Powder Recommendation: Optional Configurations for Coastal Areas/High UV-exposure Regions
	Glass	Fixed: 5mm+20Ar+5mm Glass Rabbet:40mm
		Sash：5mm+20Ar+5mm Glass Rabbet:38mm
	Hardware	Handle: LEAWOD
		Transmission: LEAWOD
	Technologies	Frame: Non-integral Welding Sash: Seamless Welding Frame & Sash:No Foaming Non-integral Welded Glazing Bead