




MCY170

WOOD CLAD ALUMINUM
SIDE-PRESSURE SLIDING WINDOW


侧压窗



Opening Types
开启方式



Item	Configuration	类型	参数
Wood Clad Aluminum Composite Profile	Profile Thickness:170mm	木铝复合型材	截面厚度：170mm
Aluminum Alloy Profile	Thickness: ≥1.80mm Standard Powder: Autria Tiger Powder Spraying Optional Powder: 10/15-Year Weathering-Resistant Fluorocarbon Powder or 20-Year Weathering-Resistant Fluorocarbon Powder Powder Recommendation: Optional Configurations for Coastal Areas/High UV-exposure Regions	铝合金型材	壁厚：≥1.80mm 粉末标配：奥地利老虎粉末 粉末选配：耐候10年/15年含氟粉末/耐候20年氟碳粉末 粉末建议：沿海地区/强紫外线照射地区采用选配配置
Wood Profile	Thickness: 18mm Standard Wood Species: American Oak Optional Wood Species: China Chestnut / Indonesian Merbau / Burmese Teak / African Padauk	木型材	厚度：18mm 木种标配：美国橡木 木种选配：国产栗木/印尼菠萝格/缅甸柚木/非洲紫檀木
Glass	Fixed:6mm+27Ar+6mm Glass Rabbet:50mm Sash:6mm+20Ar+6mm Glass Rabbet:38mm Guardrail Glass:8mm+1.52PVB+8mm Height:1100mm	玻璃	固玻：标配6mm+27Ar+6mm 玻璃槽口：50mm 扇玻：标配6mm+20Ar+6mm 玻璃槽口：38mm 护栏玻璃：标配8mm+1.52PVB+8mm 高度：1100mm
Hardware	Glass Sash Handle: LEAWOD Transmission: LEAWOD	五金配置	玻扇 执手：良木道 传动：良木道定制
Technologies	Aluminum Alloy Wood Seamless Welding/Non-return Drainage System/R7 Round Corner Three times of primer and two times of finish waterborne paint Whole Spraying	工艺	铝合金 无缝整体焊接、地漏式排水、安全圆角 木材 三底两面环保水性漆 整体喷涂



Guardrail glass for added safety(optional)
护栏玻璃更安全(可选配)

Concealed drainage system
—rain water is less likely to backflow
隐藏式排水系统，雨水不易倒灌

Frame cavity foaming process to eliminate water seepage in profile cavities
框腔体发泡工艺，杜绝型材腔体渗水



Multi-cavity structure provides greater stability
多腔体结构更稳定

Globally sourced premium hardwoods (e.g., oak, teak, Padauk) with customizable colors
精选全球优质的硬木，如：橡木、柚木、紫檀木等
可定制颜色

Compression sealing — locking points press
压紧式密封，关闭后锁点压紧牢固